

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/054736 A1

(51) International Patent Classification⁷: F16L 33/01,
33/22, 27/08

(21) International Application Number:
PCT/GB2004/004375

(22) International Filing Date: 13 October 2004 (13.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0326068.4 7 November 2003 (07.11.2003) GB

(71) Applicants (for all designated States except US): TRW SYSTEMS LIMITED [GB/GB]; Stratford Road, Solihull, West Midlands B90 4AX (GB). TRW ADVANCED PLASTICS TECHNOLOGIES GMBH & CO KG [DE/DE]; Am Schreinerstiech 4, D-95100 Selb (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MCKENNY, Aaron,


(74) Agents: BALDWIN, Mark et al.; R G C Jenkins & Co, 26 Caxton Street, London SW1H 0RJ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: A HOSE



(57) Abstract: A hose has a connector (12) at an end portion (10) thereof for providing a connection with a unit, the connector comprising a first moulded member (20) having an inner annular surface (22) moulded to an outer annular surface (24) of the end portion to provide a fluid-tight connection with the end portion, and a fastener (26) for fastening the connector to the unit. A method of manufacturing the hose comprises the steps of: inserting a core (80) inside the hose end portion (10) to support the hose end portion during moulding; moulding the first moulded member (20) with the inner annular surface (22) thereof moulded to an outer annular surface (24) of the end portion; withdrawing the core; and positioning the fastener (26) at the end portion for fastening the connector to the unit.

WO 2005/054736 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*